

**Section 3B.XX Do Not Block Intersection Marking**

Option:

Do Not Block Intersection markings may be used to mark the edges of an intersection area which is in close proximity to a signalized intersection, railroad crossing, or other nearby traffic control that may cause vehicles to stop within the intersection and impede other traffic entering the intersection.

Deleted: non-signalized

**Guidance:**

Deleted: Standard

If used, the Do Not Block Intersection markings should consist of wide solid white lines that outline the area of the intersection. For additional emphasis, normal width white crosshatching may be used inside the box (see **Figures 3B.xx and 3B.yv**).

Deleted: If used, Do Not Block Intersection markings shall consist of 12 inch solid white lines that form a box to delineate the area of the intersection where vehicles should not stop or impede other traffic entering the intersection, as shown in F

(we will describe crosshatching .. Gene British manual)

**Standard:**

**Do Not Block Intersection markings shall not be used unless accompanied by a Do Not Block Intersection (R10-7) sign.**

Option:

The Do Not Block Intersection markings may be used at other locations with appropriate signs, if authorized by law.

Word markings such as, "DO NOT BLOCK" or "KEEP CLEAR", may be used within the Do Not Block Intersection Marking box, consistent with Section 3B.19.

[This needs to go to RWSTC for consideration of signing]

Deleted: Normal width white crosshatching may also be used within the Do Not Block Intersection box.¶